

	DERMAUTOLOGY DILUYENTE DIFUMINADOS Código: DA180/1	
-------------------------------------------------------------------------------------	--------------------------------------------------------------	-------------------------------------------------------------------------------------

Version: 12 Revision: 07/02/2022



Previous revision: 14/11/2019

Date of printing: 16/02/2023

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING


1.1	IDENTIFICADOR DEL PRODUCTO: DERMAUTOLOGY DILUYENTE DIFUMINADOS WVTY-MX56-600S-J4T9 Código: DA180/1	
1.2	RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST: <u>Intended uses (main technical functions):</u> Thinner for the application of paints and varnishes. <u>Sectors of use:</u> Industrial manufacturing (SU3). Professional uses (SU22). <u>Uses advised against:</u> This product is not recommended for any use or sector of use (industrial, professional or consumer) other than those previously listed as 'Intended or identified uses'. This product is for the professional painting of vehicles only after reference to the manufacturer's data sheet. <u>Restrictions on manufacture, placing on market and use, according to Annex XVII of Regulation (EC) No. 1907/2006:</u> Not restricted.	<input type="checkbox"/> Industrial <input checked="" type="checkbox"/> Professional <input type="checkbox"/> Consumers
1.3	DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET: PRODUCTOS DISANFE, S.L. c/ Carles Riba 13 - Polígono Sector E - 08170 - Montornès del Vallès (Barcelona) Phone: +34 93 5686266 - Fax: +34 93 5686267 <u>E-mail address of the person responsible for the Safety Data Sheet:</u> disanfe@productosdisanfe.com	
1.4	EMERGENCY TELEPHONE NUMBER: National emergency telephone number: 112	


SECTION 2 : HAZARDS IDENTIFICATION

2.1	CLASSIFICATION OF THE SUBSTANCE OR MIXTURE: Classification of mixtures is carried out in accordance with the following principles: a) when data (tests) for the classification of mixtures are available, generally is carried out based on these data, b) in the absence of data (tests) for mixtures are generally used interpolation or extrapolation methods of assessing the risk, using the available data for mixtures similarly classified, and c) in the absence of tests and information which would allow to apply interpolation or extrapolation techniques, methods are used to classify risk assessment based on the data of the individual components in the mixture. <u>Classification in accordance with Regulation (EU) No. 1272/2008~2020/1182 (CLP):</u> DANGER: Flam. Liq. 3:H226 Skin Irrit. 2:H315 Eye Irrit. 2:H319 STOT SE (irrit.) 3:H335 STOT SE (narcosis) 3:H336 STOT RE 2:H373 Asp. Tox. 1:H304 Aquatic Chronic 3:H412 EUH066					
	Danger class	Classification of the mixture	Cat.	Routes of exposure	Target organs	Effects
	<u>Physicochemical:</u> 	Flam. Liq. 3:H226 Skin Irrit. 2:H315 Eye Irrit. 2:H319	c) c) c)	Cat.3 Cat.2 Cat.2	- Skin Eyes	- Skin Eyes Irritation Irritation
	<u>Human health:</u> 	STOT SE (irrit.) 3:H335 STOT SE (narcosis) 3:H336 STOT RE 2:H373i Asp. Tox. 1:H304	c) c) c) c)	Cat.3 Cat.3 Cat.2 Cat.1	Inhalation Inhalation Inhalation Ingestion+Aspiration	Respiratory tract CNS Systemic Lungs Dead
	<u>Environment:</u>	Aquatic Chronic 3:H412 EUH066	c) c)	Cat.3 -	- Skin	- Dryness, Cracking

Full text of hazard statements mentioned is indicated in section 16.

Note: When in section 3 a range of percentages is used, the health and environmental hazards describe the effects of the highest concentration of each component, but below the maximum value.





2.2	LABEL ELEMENTS: 	This product is labelled with the signal word DANGER in accordance with Regulation (EU) No. 1272/2008~2020/1182 (CLP)
	<u>Hazard statements:</u> H226 Flammable liquid and vapour. H373i May cause damage to organs through prolonged or repeated exposure if inhaled. H304 May be fatal if swallowed and enters airways. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.	
	<u>Precautionary statements:</u> P102-P405 Keep out of reach of children. Store locked up. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280F Wear protective gloves, clothing and eye protection. In case of inadequate ventilation wear respiratory protection. P301+P310+P330+P331 IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting.	

DERMATOLOGY DILUYENTE DIFUMINADOS Código: DA180/1		  	
P303+P361+P353-P352-P312 P305+P351+P338-P310 P273-P501a Supplementary statements: None. Substances that contribute to classification: n-butyl acetate Xylene (mixture of isomers) 2-methoxy-1-methylethyl acetate Hydrocarbons C9 aromatics	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash with plenty of soap and water. Call a POISON CENTER or doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. Avoid release to the environment. Dispose of content/s container in accordance with local regulations.		
2.3	OTHER HAZARDS: Hazards which do not result in classification but which may contribute to the overall hazards of the mixture: Other physicochemical hazards: Vapours may form with air a mixture potentially flammable or explosive. Other adverse human health effects: No other relevant adverse effects are known. Other negative environmental effects: Does not contain substances that fulfil the PBT/vPvB criteria.		
SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS			
3.1	SUBSTANCES: Not applicable (mixture).		
3.2	MIXTURES: This product is a mixture. Chemical description: Mixture of organic solvents. HAZARDOUS INGREDIENTS: Substances taking part in a percentage higher than the exemption limit:		
50 < 60 %  	n-butyl acetate CAS: 123-86-4 , EC: 204-658-1 CLP: Warning: Flam. Liq. 3:H226 STOT SE (narcosis) 3:H336 EUH066	REACH: 01-2119485493-29	Index No. 607-025-00-1 < REACH / ATP01
25 < 30 %   	Xylene (mixture of isomers) CAS: 1330-20-7 , EC: 215-535-7 CLP: Danger: Flam. Liq. 3:H226 Acute Tox. (inh.) 4:H332 Acute Tox. (skin) 4:H312 Skin Irrit. 2:H315 Eye Irrit. 2:H319 STOT SE (irrit.) 3:H335 STOT RE 2:H373i Asp. Tox. 1:H304	REACH: 01-2119488216-32	Index No. 601-022-00-9 < REACH
10 < 15 %  	2-methoxy-1-methylethyl acetate CAS: 108-65-6 , EC: 203-603-9 CLP: Warning: Flam. Liq. 3:H226 STOT SE (narcosis) 3:H336	REACH: 01-2119475791-29	Index No. 607-195-00-7 < REACH
10 < 15 %   	Hydrocarbons C9 aromatics (CAS: 64742-95-6) , List No. 918-668-5 CLP: Danger: Flam. Liq. 3:H226 STOT SE (irrit.) 3:H335 STOT SE (narcosis) 3:H336 Asp. Tox. 1:H304 Aquatic Chronic 2:H411 EUH066	REACH: 01-2119455851-35	Autoclassified < REACH
1 < 2,5 % 	Butylglycol acetate CAS: 112-07-2 , EC: 203-933-3 CLP: Warning: Acute Tox. (inh.) 4:H332 Acute Tox. (skin) 4:H312 Acute Tox. (oral) 4:H302	REACH: 01-2119475112-47	Index No. 607-038-00-2 < REACH
	Impurities: Does not contain other components or impurities which will influence the classification of the product. Stabilizers: None Reference to other sections: For more information on hazardous ingredients, see sections 8, 11, 12 and 16. SUBSTANCES OF VERY HIGH CONCERN (SVHC): List updated by ECHA on 08/07/2021. Substances SVHC subject to authorisation, included in Annex XIV of Regulation (EC) no. 1907/2006: None Substances SVHC candidate to be included in Annex XIV of Regulation (EC) no. 1907/2006: None PERSISTENT, BIOACCUMULABLE AND TOXIC PBT, OR VERY PERSISTENT AND VERY BIOACCUMULABLE VPVB SUBSTANCES: Does not contain substances that fulfil the PBT/vPvB criteria.		

	DERMAUTOLOGY DILUYENTE DIFUMINADOS Código: DA180/1
-------------------------------------------------------------------------------------	--------------------------------------------------------------

SECTION 4 : FIRST AID MEASURES4.1 **DESCRIPTION OF FIRST-AID MEASURES:**

Symptoms may occur after exposure, so that in case of direct exposure to the product, when in doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Lifeguards should pay attention to self-protection and use the recommended protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid. It can be dangerous to the person giving artificial respiration by mouth-to-mouth (the kiss of life).

Route of exposure	Symptoms and effects, acute and delayed	Description of first-aid measures
Inhalation: 	Inhalation of solvent vapours may produce headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, unconsciousness. Inhalation produces irritation to mucus, coughing and breathlessness.	Remove the patient out of the contaminated area into the fresh air. If breathing is irregular or stops, administer artificial respiration. If the person is unconscious, place in appropriate recovery position. Keep the patient warm and at rest until medical attention arrives.
Skin: 	Skin contact causes redness. Prolonged contact may cause skin dryness.	Remove immediately contaminated clothing. Wash thoroughly the affected area with plenty of cold or lukewarm water and neutral soap, or use a suitable skin cleanser.
Eyes: 	Contact with the eyes produces redness and pain.	Remove contact lenses. Rinse eyes copiously by irrigation with plenty of clean, fresh water for at least 15 minutes, holding the eyelids apart, until the irritation is reduced. Call a physician immediately.
Ingestion: 	If swallowed, may cause irritation of the throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea.	If swallowed, seek medical advice immediately and show container or label. Do not induce vomiting, due to the risk of aspiration. Keep the patient at rest.

4.2 **MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:**

The main symptoms and effects are indicated in sections 4.1 and 11.1

4.3 **INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:**

Notes to physician: The product inhaled during vomiting could cause lung damage. Thus, emesis should not be induced, neither mechanically nor pharmacologically. In the case of ingestion, empty the stomach with caution.

Antidotes and contraindications: Specific antidote not known. In the case of a pneumonia by chemical agents, must be considered a therapy with antibiotics and corticosteroids.

SECTION 5 : FIRE-FIGHTING MEASURES5.1 **EXTINGUISHING MEDIA:**

Extinguishing powder or CO₂. In the case of more important fires, also alcohol resistant foam and water spray/mist. Do not use for extinguishing: direct water jet. Direct water jet may not be effective to extinguish the fire, since the fire may spread.

5.2 **SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:**

Flammable liquid and vapour. Fire can produce a dense black smoke. As consequence of combustion or thermal decomposition, hazardous products may be produced: carbon monoxide, carbon dioxide. Harmful. Irritant. Exposure to combustion or decomposition products may be a hazard to health.

5.3 **ADVICE FOR FIREFIGHTERS:**

Special protective equipment: Depending on magnitude of fire, heat-proof protective clothing may be required, appropriate independent breathing apparatus, gloves, protective glasses or face masks and boots. If the fire-proof protective equipment is not available or is not being used, combat fire from a sheltered position or from a safe distance. The standard EN469 provides a basic level of protection for chemical incidents.

Other recommendations: Cool with water the tanks, cisterns or containers close to sources of heat or fire. Bear in mind the direction of the wind. Do not allow fire-fighting residue to enter drains, sewers or water courses.

SECTION 6 : ACCIDENTAL RELEASE MEASURES6.1 **PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:**

Eliminate possible sources of ignition and when appropriate, ventilate the area. Do not smoke. Avoid direct contact with this product. Avoid breathing vapours. Keep people without protection in opposition to the wind direction.

6.2 **ENVIRONMENTAL PRECAUTIONS:**

Avoid contamination of drains, surface or subterranean water and soil. In the case of large scale spills or when the product contaminates lakes, rivers or sewages, inform the appropriate authorities in accordance with local regulations.

6.3 **METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:**

Contain and mop up spills with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc..). Keep the remains in a closed container.

6.4 **REFERENCE TO OTHER SECTIONS:**

For contact information in case of emergency, see section 1.
 For information on safe handling, see section 7.
 For exposure controls and personal protection measures, see section 8.
 For waste disposal, follow the recommendations in section 13.

DERMA
AUTO
LOGY

A

DERMAUTOLOGY DILUYENTE DIFUMINADOS
Código: DA180/1

**SECTION 7 : HANDLING AND STORAGE**

7.1

PRECAUTIONS FOR SAFE HANDLING:

Comply with the existing legislation on health and safety at work.

General recommendations:

Avoid any type of leakage or escape. Keep the container tightly closed.

Recommendations for the prevention of fire and explosion risks:

Vapours are heavier than air, may spread along floors to a considerable distance, can form explosive mixtures with air and are able to reach distant ignition sources and flame up or explode. Due to its flammability, this material should only be used in areas from which all naked lights and other sources of ignition have been excluded and away from other heat or electrical sources. Switch mobile phones off and do not smoke. If this product is used in an industrial installation, the zones with risk of explosion should be marked. Use instruments, systems and protective equipment adequate to the classification of zones, according to the health and safety at work laws, in accordance with Directive 2016/34/EU and 99/92/EC. Electrical equipment should be protected to the appropriate standard. No tools with a potential for sparks should be used. Floors should be electrically conductive and operators should wear anti-static footwear and clothing. Elaborate the document 'Protection against explosions'.

- Flash point	:		27*	°C
- Autoignition temperature	:		385*	°C
- Lower/upper flammability or explosive limits	:	#	1.3* - 7.7*	% Volume 25°C
- Ventilation requirement	:		140.	m3/l

Air/Preparation

to keep below 1/10 of the Lower Explosive Limit.

Recommendations for the prevention of toxicological risks:

Do not eat, drink or smoke while handling. After handling, wash hands with soap and water. For exposure controls and personal protection measures, see section 8.

Recommendations for the prevention of environmental contamination:

Avoid any spillage in the environment. Pay special attention to the cleaning water. In the case of accidental spillage, follow the instructions indicated in section 6.

7.2

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:

Forbid the entry to unauthorized persons. Keep out of reach of children. This product should be stored isolated from heat and electrical sources. Do not smoke in storage area. If possible, avoid direct contact with sunlight. Avoid extreme humidity conditions. In order to avoid leakages, the containers, after use, should be closed carefully and placed in a vertical position. For more information, see section 10.

Class of storage : According to current legislation.

Temperature interval : min: 5. °C, max: 40. °C (recommended).

Incompatible materials:

Keep away from oxidizing agents, acids, alkalis, metals, peroxides.

Type of packaging:

According to current legislation.

Limit quantity (Seveso III): Directive 2012/18/EU:

- Named dangerous substances/mixtures: None
- Hazard categories and lower-/upperthreshold quantities in tonnes (t):
- Physical hazards: Flammable liquid and vapour (P5c) (5000t/50000t).
- Health hazards: Not applicable
- Environmental hazards: Not applicable
- Other hazards: Not applicable.
- Threshold quantity for the application of lower-tier requirements: 5000 tons
- Threshold quantity for the application of upper-tier requirements: 50000 tons
- Remarks:

The qualifying quantities set out above relate to each establishment. The quantities to be considered for the application of the relevant Articles are the maximum quantities which are present or are likely to be present at any one time. Dangerous substances present at an establishment only in quantities equal to or less than 2 % of the relevant qualifying quantity shall be ignored for the purposes of calculating the total quantity present, if their location within an establishment is such that it cannot act as an initiator of a major accident elsewhere at that establishment. For more details, see note 4 of Annex I of the Seveso Directive.

7.3

SPECIFIC END USES:

For the use of this product particular recommendations apart from that already indicated are not available.

DERMAUTOLOGY DILUYENTE DIFUMINADOS
Código: DA180/1

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1

CONTROL PARAMETERS:

If a product contains ingredients with exposure limits, may be necessary a personnel monitoring, work place or biological, to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to EN689, EN14042 and EN482 standard concerning methods for assessing the exposure by inhalation to chemical agents, and exposure to chemical and biological agents. Reference should be also made to national guidance documents for methods for the determination of dangerous substances.

OCCUPATIONAL EXPOSURE LIMIT VALUES (TLV)

AGCIH 2020	Year	TLV-TWA		TLV-STEL		Remarks
		ppm	mg/m ³	ppm	mg/m ³	
n-butyl acetate	2015	50.	237.	150.	713.	A4 , BEI Recommended Skin
Xylene	1996	100.	434.	150.	651.	
2-methoxy-1-methylethyl acetate		50.	275.	100.	550.	
Hydrocarbons C9 aromatics		50.	290.	-	-	Recommended A3
Butylglycol acetate	2000	20.	133.	-	-	

TLV - Threshold Limit Value, TWA - Time Weighted Average, STEL - Short Term Exposure Limit.

Skin - Danger of cutaneous absorption.

A3 - Carcinogenic in animals.

A4 - Non classified as carcinogenic in humans.

BEI - Biological exposure index (biological monitoring).

Dermal (Vd): Means that, in exposures to this substance, the contribution by the cutaneous route, including the mucous membranes and eyes, may result significant for the overall body content if no measures are taken to prevent absorption. There are some chemicals for which dermal absorption, both in liquid and vapour phases, can be very high, and this route of entry may be or equal or greater importance even than inhalation pathway. In these situations, the use of a biological control is essential in order to quantify the overall amount of contaminant absorbed.

BIOLOGICAL LIMIT VALUES:

Biological monitoring can be a very useful complementary technique to air monitoring when air sampling techniques alone may not give a reliable indication of exposure. Biological monitoring is the measurement and assessment of hazardous substances or their metabolites in tissues, secretions, excreta or expired air, or any combination of these, in exposed workers. Measurements reflect absorption of a substance by all routes. Biological monitoring may be particularly useful in circumstances where there is likely to be significant skin absorption and/or gastrointestinal tract uptake following ingestion, where control of exposure depends on respiratory protective equipment, where there is a reasonably well-defined relationship between biological monitoring and effect, or where it gives information on accumulated dose and target organ body burden which is related to toxicity.

This preparation contains the following substances that have established a biological limit value:

- Xylenes (technical or commercial grade) (2011): Biological determinant: methylhippuric acids in urine, BEI: 1.5 g/g creatinine,

Sampling time: end of shift (2).

(2) When the end of the exposition not coincide with the end of the working day, the sample will be taken as soon as possible after the real exposition ceases.

DERIVED NO-EFFECT LEVEL (DNEL):

Derived no-effect level (DNEL) is a level of exposure that is considered safe, derived from toxicity data according to specific guidances included in REACH. DNEL values may differ from an occupational exposure limit (OEL) for the same chemical. OEL values may come recommended by a particular company, a government regulatory agency or an organization of experts. Although considered protective of health, the OEL values are derived by a process different of REACH.

Derived no-effect level, workers:

- Systemic effects, acute and chronic:

	DNEL Inhalation mg/m ³		DNEL Cutaneous mg/kg bw/d		DNEL Oral mg/kg bw/d	
n-butyl acetate	960. (a)	480. (c)	11.0 (a)	11.0 (c)	- (a)	- (c)
Xylene (mixture of isomers)	289. (a)	77.0 (c)	s/r (a)	180. (c)	- (a)	- (c)
2-methoxy-1-methylethyl acetate	- (a)	275. (c)	- (a)	153. (c)	- (a)	- (c)
Hydrocarbons C9 aromatics	- (a)	150. (c)	- (a)	25.0 (c)	- (a)	- (c)
Butylglycol acetate	775. (a)	133. (c)	102. (a)	102. (c)	- (a)	- (c)

Derived no-effect level, workers:

- Local effects, acute and chronic:

	DNEL Inhalation mg/m ³		DNEL Cutaneous mg/cm ²		DNEL Eyes mg/cm ²	
n-butyl acetate	960. (a)	480. (c)	s/r (a)	s/r (c)	s/r (a)	- (c)
Xylene (mixture of isomers)	289. (a)	s/r (c)	s/r (a)	s/r (c)	- (a)	- (c)
2-methoxy-1-methylethyl acetate	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
Hydrocarbons C9 aromatics	- (a)	- (c)	- (a)	- (c)	- (a)	- (c)
Butylglycol acetate	333. (a)	s/r (c)	s/r (a)	s/r (c)	- (a)	- (c)












Derived no-effect level, general population:

Not applicable (product for professional or industrial use).

(a) - Acute, short-term exposure, (c) - Chronic, long-term or repeated exposure.

(-) - DNEL not available (without data of registration REACH).

s/r - DNEL not derived (not identified hazard).

DERM AUTO LOGY A DERMAUTOLOGY DILUYENTE DIFUMINADOS Código: DA180/1		  	
PREDICTED NO-EFFECT CONCENTRATION (PNEC):			
Predicted no-effect concentration, aquatic organisms:			
- Fresh water, marine water and intermittent release:			
n-butyl acetate	PNEC Fresh water mg/l	PNEC Marine mg/l	PNEC Intermittent mg/l
Xylene (mixture of isomers)	0.180	0.0180	0.360
2-methoxy-1-methylethyl acetate	0.327	0.327	0.327
Hydrocarbons C9 aromatics	0.635	0.0635	6.35
Butylglycol acetate	uvcb	uvcb	uvcb
	0.304	0.0304	0.560
- Wastewater treatment plants (STP) and sediments in fresh- and marine water:			
n-butyl acetate	PNEC STP mg/l	PNEC Sediments mg/kg dw/d	PNEC Sediments mg/kg dw/d
Xylene (mixture of isomers)	35.6	0.981	0.0981
2-methoxy-1-methylethyl acetate	6.58	12.5	12.5
Hydrocarbons C9 aromatics	100.	3.29	0.329
Butylglycol acetate	uvcb	uvcb	uvcb
	90.0	2.03	0.203
Predicted no-effect concentration, terrestrial organisms:			
- Air, soil and effects for predators and humans:			
n-butyl acetate	PNEC Air mg/m3	PNEC Soil mg/kg dw/d	PNEC Oral mg/kg dw/d
Xylene (mixture of isomers)	s/r	0.0903	n/b
2-methoxy-1-methylethyl acetate	-	2.31	-
Hydrocarbons C9 aromatics	-	0.290	-
Butylglycol acetate	uvcb	uvcb	uvcb
	-	0.680	60.0
(-) - PNEC not available (without data of registration REACH). s/r - PNEC not derived (not identified hazard). n/b - PNEC not derived (not bioaccumulative potential). uvcb - The substance has an unknown or variable composition (UVCB). The conventional methods to derive the PNEC are not appropriate and it is not possible to identify a single PNEC representative for these substances, and therefore not used in calculations for risk assessment.			
8.2	EXPOSURE CONTROLS: ENGINEERING MEASURES:      Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these measures are not sufficient to maintain concentrations of vapours below the Occupational Exposure Limits, suitable respiratory protection must be worn.		
	Protection of respiratory system: Avoid the inhalation of solvents. Protection of eyes and face: It is recommended to install water taps, sources or eyewash bottles with clean water close to the working area. Protection of hands and skin: It is recommended to install water taps or sources with clean water close to the working area. Barrier creams may help to protect the exposed areas of the skin. Barrier creams should not be applied once exposure has occurred.		
	OCCUPATIONAL EXPOSURE CONTROLS: Regulation (EU) No. 2016/425: As a general measure on prevention and safety in the work place, we recommend the use of a basic personal protection equipment (PPE), with the corresponding marking. For more information on personal protective equipment (storage, use, cleaning, maintenance, type and characteristics of the PPE, protection class, marking, category, CEN norm, etc.), you should consult the informative brochures provided by the manufacturers of PPE.		
	Mask: 	A-type filter mask (brown) for gases and vapours of organic compounds with a boiling point higher than 65°C (EN14387). Class 1: low capacity up to 1000 ppm, Class 2: medium capacity up to 5000 ppm, Class 3: high capacity up to 10000 ppm. In order to obtain a suitable protection level, the filter class must be selected depending on the type and concentration of the contaminating agents present, in accordance with the specifications supplied by the filter producers. The respiratory equipment with filters does not work satisfactorily when the air contains high concentrations of vapour or oxygen content less than 18% in volume. In presence of high concentrations of vapour, use independent breathing apparatus.	
	Safety goggles: 	Safety goggles designed to protect against liquid splashes, with suitable lateral protection (EN166). Clean daily and disinfect at regular intervals in accordance with the instructions of the manufacturer.	
	Face shield:	No.	
	Gloves: 	Solvent-resistant gloves (EN374). When repeated or prolonged contact with the product is expected, gloves of protection level 5 or higher should be used, with a breakthrough time of >240 min. When short contact with the product is expected, use gloves with a protection level 2 or higher should be used, with a breakthrough time >30 min. The breakthrough time of the selected glove material should be in accordance with the pretended period of use. There are several factors (for example, temperature), they do in practice the period of use of a protective gloves resistant against chemicals is clearly lower than the established standard EN374. Due to the wide variety of circumstances and possibilities, the instructions/specifications provided by the glove supplier should be taken into account. Use the proper technique of removing gloves (without touching glove's outer surface) to avoid contact of the product with the skin. The gloves should be immediately replaced when any sign of degradation is noted.	
	Boots:	No.	
	Apron:	No.	

D A	DERMAUTOLOGY DILUYENTE DIFUMINADOS Código: DA180/1	  
--------	-------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Clothing: Advisable.

Thermal hazards:

Not applicable (the product is handled at room temperature).

ENVIRONMENTAL EXPOSURE CONTROLS:

Avoid any spillage in the environment. Avoid any release into the atmosphere.

Spills on the soil: Prevent contamination of soil.

Spills in water: Do not allow to escape into drains, sewers or water courses.

- **Water Management Act:** This product does not contain any substance included in the list of priority substances in the field of water policy under Directive 2000/60/EC~2013/39/EU.

Emissions to the atmosphere: Because of volatility, emissions to the atmosphere while handling and use may result, in special when it is used as a solvent. Avoid any solvent release into the atmosphere.

- **VOC (industrial installations):** If this product is used in an industrial installation, it must be verified if it is applicable the Directive 2010/75/EC, on the limitation of emissions of volatile compounds due to the use of organic solvents in certain activities and installations: Solvents : 100.0% Weight , VOC (supply) : 100.0% Weight , VOC : 70.9% C (expressed as carbon) , Molecular weight (average) : 117.5 , Number C atoms (average) : 6.9.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1 **INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:**

Appearance

- Physical state : Liquid.
- Colour : Colourless.
- Odour : Characteristic.

pH-value

- pH : Not applicable (non-aqueous media).

Change of state

- Melting point : Not applicable (mixture).
- Initial boiling point : 126.3* °C at 760 mmHg

Density

- Vapour density : 3.95* at 20°C 1 atm. Relative air
- Relative density : 0.89* at 20/4°C Relative water

Stability

Viscosity:

- Dynamic viscosity : 0.78 cps 20°C
- Kinematic viscosity : 0.30 mm²/s at 40°C

Volatility:

- Evaporation rate : 80.7* nBuAc=100 25°C Relative
- Vapour pressure : 6.8* mmHg at 20°C
- Vapour pressure : 4.6* kPa at 50°C

Solubility(ies)

- Solubility in water: : Insoluble.
- Partition coefficient: n-octanol/water : Not applicable (mixture).

Flammability:

- Flash point : 27* °C
- Lower/upper flammability or explosive limits : # 1.3* - 7.7* % Volume 25°C
- Autoignition temperature : 385* °C

Explosive properties:

Vapours can form explosive mixtures with air and are able to flame up or explode in presence of an ignition source.

Oxidizing properties:

Not classified as oxidizing product.

*Estimated values based on the substances composing the mixture.

9.2 **OTHER INFORMATION:**

- Surface tension : 20.3* din/cm at 20°C
- Heat of combustion : 7915* Kcal/kg
- VOC (supply) : 100.0 % Weight
- VOC (supply) : 889.9 g/l

The values indicated do not always coincide with product specifications. The data for the product specifications can be found in the corresponding technical data sheet. For additional information concerning physical and chemical properties related to safety and environment, see sections 7 and 12.

SECTION 10 : STABILITY AND REACTIVITY

10.1 **REACTIVITY:**

Corrosivity to metals: It is not corrosive to metals.

Pyrophorical properties: It is not pyrophoric.

10.2 **CHEMICAL STABILITY:**

Stable under recommended storage and handling conditions.

10.3 **POSSIBILITY OF HAZARDOUS REACTIONS:**

Possible dangerous reaction with oxidizing agents, acids, alkalis, metals, peroxides.

	DERMAUTOLOGY DILUYENTE DIFUMINADOS Código: DA180/1
-------------------------------------------------------------------------------------	--------------------------------------------------------------

10.4 CONDITIONS TO AVOID:
 - **Heat:** Keep away from sources of heat.
 - **Light:** If possible, avoid direct contact with sunlight.
 - **Air:** The product is not affected by exposure to air, but should not be left the containers open.
 - **Humidity:** Avoid extreme humidity conditions.
 - **Pressure:** Not relevant.
 - **Shock:** The product is not sensitive to shocks, but as a recommendation of a general nature should be avoided bumps and rough handling to avoid dents and breakage of packaging, especially when the product is handled in large quantities, and during loading and download operations.

10.5 INCOMPATIBLE MATERIALS:
 Keep away from oxidizing agents, acids, alkalis, metals, peroxides.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS:
 As consequence of thermal decomposition, hazardous products may be produced: carbon monoxide.

SECTION 11 : TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation is available. The toxicological classification for these mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2020/1182 (CLP).

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

Dose and lethal concentrations

for individual ingredients :

n-butyl acetate
 Xylene (mixture of isomers)
 2-methoxy-1-methylethyl acetate
 Hydrocarbons C9 aromatics
 Butylglycol acetate

LD50 (OECD 401)

mg/kg bw oral

10768. Rat
 4300. Rat
 8532. Rat
 3592. Rat
 1880. Rat

LD50 (OECD 402)

mg/kg bw cutaneous

17600. Rabbit
 1700. Rabbit
 > 5000. Rat
 3160. Rabbit
 1480. Rabbit

LC50 (OECD 403)

mg/m³ 4h inhalation

> 23400. Rat
 > 22080. Rat
 > 35700. Rat
 > 6193. Rat
 > 400. Rat

Estimates of acute toxicity (ATE)

for individual ingredients :

Xylene (mixture of isomers)
 Butylglycol acetate

ATE

mg/kg bw oral

-
 1880.

ATE

mg/kg bw cutaneous

1100.*
 1480.

ATE

mg/m³ 4h inhalation

11000.* Vapours
 11000.* Vapours

(*) - Point estimates of acute toxicity corresponding to the classification category (see GHS/CLP Table 3.1.2). These values are designed to be used in the calculation of the ATE for classification of a mixture based on its components and do not represent test results.

(-) - The components that are assumed to have no acute toxicity at the upper threshold of category 4 for the corresponding exposure route are ignored.

No observed adverse effect level

Not available





Lowest observed adverse effect level

Not available







INFORMATION ON LIKELY ROUTES OF EXPOSURE: Acute toxicity:

Routes of exposure	Acute toxicity	Cat.	Main effects, acute and/or delayed	Criteria
<u>Inhalation:</u> Not classified	ATE > 20000 mg/m ³	-	Not classified as a product with acute toxicity if inhaled (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
<u>Skin:</u> Not classified	ATE > 2000 mg/kg bw	-	Not classified as a product with acute toxicity in contact with skin (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.
<u>Eyes:</u> Not classified	Not available	-	Not classified as a product with acute toxicity by eye contact (lack of data).	GHS/CLP 1.2.5.
<u>Ingestion:</u> Not classified	ATE > 2000 mg/kg bw	-	Not classified as a product with acute toxicity if swallowed (based on available data, the classification criteria are not met).	GHS/CLP 3.1.3.6.

GHS/CLP 3.1.3.6: Classification of mixtures based on ingredients of the mixture (additivity formula).

	DERMATOLOGY DILUYENTE DIFUMINADOS Código: DA180/1	  
----------------------------------------------------------------------------------	-------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

CORROSION / IRRITATION / SENSITISATION :

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
<u>Respiratory corrosion/irritation:</u> 	Respiratory tract 	Cat. 3	IRRITANT: May cause respiratory irritation.	GHS/CLP 1.2.6. 3.8.3.4.
<u>Skin corrosion/irritation:</u> 	Skin 	Cat. 2	IRRITANT: Causes skin irritation.	GHS/CLP 3.2.3.3.
<u>Serious eye damage/irritation:</u> 	Eyes 	Cat. 2	IRRITANT: Causes serious eye irritation.	GHS/CLP 3.3.3.3.
<u>Respiratory sensitisation:</u> Not classified	-	-	Not classified as a product sensitising by inhalation (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.
<u>Skin sensitisation:</u> Not classified	-	-	Not classified as a product sensitising by skin contact (based on available data, the classification criteria are not met).	GHS/CLP 3.4.3.3.



GHS/CLP 3.2.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.3.3.3: Classification of the mixture when data are available for all components or only for some components.

GHS/CLP 3.4.3.3: Classification of the mixture when data are available for all components or only for some components.








GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

ASPIRATION HAZARD:

Danger class	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
<u>Aspiration hazard:</u> 	Lungs 	Cat. 1	HAZARD OF ASPIRATION: Maybe fatal if swallowed and enters airways.	GHS/CLP 3.10.3.3.

GHS/CLP 3.10.3.3: Classification of the mixture when data are available for all components or only for some components.

SPECIFIC TARGET ORGANS TOXICITY (STOT): Single exposure (SE) and/or Repeated exposure (RE):

Effects	SE/RE	Target organs	Cat.	Main effects, acute and/or delayed	Criteria
<u>Systemic:</u> 	RE	Systemic 	Cat. 2	HARMFUL: May cause damage to organs through prolonged or repeated exposure if inhaled.	GHS/CLP 3.8.3.4.
<u>Respiratory:</u> 	SE	Respiratory tract 	Cat. 3	IRRITANT: May cause respiratory irritation.	GHS/CLP 3.8.3.4.
<u>Cutaneous:</u>	RE	Skin 	-	DEFATTENING: Repeated exposure may cause skin dryness or cracking.	GHS/CLP 1.2.4.
<u>Neurological:</u> 	SE	CNS 	Cat. 3	NARCOSIS: May cause drowsiness or dizziness if inhaled.	GHS/CLP 3.8.3.4.

GHS/CLP 3.8.3.4: Classification of the mixture when data are available for all components or only for some components.

CMR EFFECTS:

Carcinogenic effects: It is not considered as a carcinogenic product.

Genotoxicity: It is not considered as a mutagenic product.

Toxicity for reproduction: Does not harm fertility. Does not harm the unborn child.

Effects via lactation: Not classified as a hazardous product for children breast-fed.

DELAYED AND IMMEDIATE EFFECTS AS WELL AS CHRONIC EFFECTS FROM SHORT AND LONG-TERM EXPOSURE:

Routes of exposure: May be absorbed by inhalation of vapour, through the skin and by ingestion.

Short-term exposure: Exposure to solvent vapour concentrations in excess of the stated occupational exposure limit, may result in adverse health effects, such as mucous membrane and respiratory system irritation and adverse effects on kidneys, liver and central nervous system. Liquid splashes in the eyes may cause irritation and reversible damage. Very small amounts aspirated by the lungs may cause severe pulmonary damage, including death. If swallowed, may cause irritation of the throat and other effects may be the same as described in the exposure to vapours.

Long-term or repeated exposure: Repeated or prolonged contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Repeated exposure may cause skin dryness or cracking.

INTERACTIVE EFFECTS:

Not available.

INFORMATION ABOUT TOXICOKINETICS, METABOLISM AND DISTRIBUTION:Dermal absorption:

This preparation contains the following substances for which dermal absorption can be very high: 2-methoxy-1-methylethyl acetate.

Basic toxicokinetics: Not available.

D A	DERMAUTOLOGY DILUYENTE DIFUMINADOS Código: DA180/1	  
--------	-------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

ADDITIONAL INFORMATION:

This preparation contains glycols that are readily absorbed through the skin and may cause harmful effects on the blood.

SECTION 12 : ECOLOGICAL INFORMATION

No experimental ecotoxicological data on the preparation as such is available. The ecotoxicological classification for the mixture has been carried out by using the conventional calculation method of the Regulation (EU) No. 1272/2008~2020/1182 (CLP).

12.1 TOXICITY:

<u>Acute toxicity in aquatic environment</u> for individual ingredients :	<u>LC50</u> (OECD 203) mg/l-96hours	<u>EC50</u> (OECD 202) mg/l-48hours	<u>EC50</u> (OECD 201) mg/l-72hours
n-butyl acetate	> 18. Fishes	> 44. Daphnia	675. Algae
Xylene (mixture of isomers)	> 13. Fishes	> 16. Daphnia	> 10. Algae
2-methoxy-1-methylethyl acetate	134. Fishes	408. Daphnia	> 1000. Algae
Hydrocarbons C9 aromatics	> 9.2 Fishes	> 3.2 Daphnia	> 2.9 Algae
Butylglycol acetate	> 28. Fishes	> 37. Daphnia	1570. Algae

<u>No observed effect concentration</u>	<u>NOEC</u> (OECD 210) mg/l-28days	<u>NOEC</u> (OECD 211) mg/l-21days	<u>NOEC</u> (OECD 201) mg/l-72hours
n-butyl acetate		23. Daphnia	
2-methoxy-1-methylethyl acetate		> 100. Daphnia	

Lowest observed effect concentration

Not available

ASSESSMENT OF AQUATIC TOXICITY:

<u>Aquatic toxicity</u>	<u>Cat.</u>	<u>Main hazards to the aquatic environment</u>	<u>Criteria</u>
<u>Acute aquatic toxicity:</u> Not classified	-	Not classified as a hazardous product with acute toxicity to aquatic life (based on available data, the classification criteria are not met).	GHS/CLP 4.1.3.5.3.
<u>Chronic aquatic toxicity:</u>	Cat. 3	HARMFUL: Harmful to aquatic life with long lasting effects.	GHS/CLP 4.1.3.5.4.

CLP 4.1.3.5.3: Classification of a mixture for acute hazards, based on summation of classified components.

CLP 4.1.3.5.4: Classification of a mixture for chronic (long term) hazards, based on summation of classified components.

12.2 PERSISTENCE AND DEGRADABILITY:

Not available.

<u>Aerobic biodegradation</u> for individual ingredients :	<u>DQO</u> mgO2/g	<u>%DBO/DQO</u> 5 days 14 days 28 days	<u>Biodegradability</u>
n-butyl acetate	2204.	~ 80. ~ 82. ~ 83.	Easy
Xylene (mixture of isomers)	2620.	~ 52. ~ 81. ~ 88.	Easy
2-methoxy-1-methylethyl acetate	1520.	~ 22. ~ 78. ~ 90.	Easy
Hydrocarbons C9 aromatics	3195.		Easy
Butylglycol acetate	2071.	~ 51. ~ 71. ~ 88.	Easy

Note: Biodegradability data correspond to an average of data from various bibliographic sources.

12.3 BIOACCUMULATIVE POTENTIAL:


May bioaccumulate.

<u>Bioaccumulation</u> for individual ingredients :	<u>log Pow</u>	<u>BCF</u> L/kg	<u>Potential</u>
n-butyl acetate	1.81	6.9 (calculated)	Not bioaccumulative.
Xylene (mixture of isomers)	3.16	56. (calculated)	Low
2-methoxy-1-methylethyl acetate	0.560	3.2 (calculated)	Not bioaccumulative.
Hydrocarbons C9 aromatics	3.30	70. (calculated)	Low
Butylglycol acetate	1.51	5.1 (calculated)	Not bioaccumulative.


12.4 MOBILITY IN SOIL:

Not available.

<u>Mobility</u> for individual ingredients :	<u>log P_{oc}</u>	<u>Constant of Henry</u> Pa-m3/mol 20°C	<u>Potential</u>
n-butyl acetate	1.84	28. (calculated)	Not bioaccumulative.
Xylene (mixture of isomers)	2.25	660. (calculated)	Low
2-methoxy-1-methylethyl acetate	0.230	0.42 (calculated)	Not bioaccumulative.
Hydrocarbons C9 aromatics	2.96	440. (calculated)	Low
Butylglycol acetate	1.41	0.32 (calculated)	Not bioaccumulative.

DERMATOLOGY DILUYENTE DIFUMINADOS Código: DA180/1			
12.5	RESULTS OF PBT AND VPVB ASSESSMENT: Annex XIII of Regulation (EC) no. 1907/2006: Does not contain substances that fulfil the PBT/vPvB criteria.		
12.6	OTHER ADVERSE EFFECTS: Ozone depletion potential: Not available. Photochemical ozone creation potential: Not available. Earth global warming potential: In case of fire or incineration liberates CO2. Endocrine disrupting potential: Not available.		
SECTION 13 : DISPOSAL CONSIDERATIONS			
13.1	WASTE TREATMENT METHODS: Directive 2008/98/EC~Regulation (EU) no. 1357/2014: Take all necessary measures to prevent the production of waste whenever possible. Analyse possible methods for revaluation or recycling. Do not discharge into drains or the environment, dispose at an authorised waste collection point. Waste should be handled and disposed in accordance with current local and national regulations. For exposure controls and personal protection measures, see section 8. Disposal of empty containers: Directive 94/62/EC~2015/720/EU, Decision 2000/532/EC~2014/955/EU: Emptied containers and packaging should be disposed in accordance with currently local and national regulations. The classification of packaging as hazardous waste will depend on the degree of emptying of the same, being the holder of the residue responsible for their classification, in accordance with Chapter 15 01 of Decision 2000/532/EC, and forwarding to the appropriate final destination. With contaminated containers and packaging, adopt the same measures as for the product in itself. Procedures for neutralising or destroying the product: Controlled incineration in special facilities for chemical waste, in accordance with local regulations.		
SECTION 14 : TRANSPORT INFORMATION			
14.1	UN NUMBER: 1263		
14.2	UN PROPER SHIPPING NAME: PAINT RELATED MATERIAL		
14.3	TRANSPORT HAZARD CLASS(ES): Transport by road (ADR 2021) and Transport by rail (RID 2021): - Class: 3 - Packing group: III - Classification code: F1 - Tunnel restriction code: (D/E) - Transport category: 3, max. ADR 1.1.3.6. 1000 L - Limited quantities: 5 L (see total exemptions ADR 3.4) - Transport document: Consignment paper. - Instructions in writing: ADR 5.4.3.4 Transport by sea (IMDG 39-18): - Class: 3 - Packing group: III - Emergency Sheet (EmS): F-E,S_E - First Aid Guide (MFAG): 310,313 - Marine pollutant: No. - Transport document: Shipping Bill of lading. Transport by air (ICAO/IATA 2021): - Class: 3 - Packing group: III - Transport document: Air Bill of lading. Transport by inland waterways (ADN): Not available.		
14.4	PACKING GROUP: See section 14.3		
14.5	ENVIRONMENTAL HAZARDS: Not applicable.		
14.6	SPECIAL PRECAUTIONS FOR USER: Ensure that persons transporting the product know what to do in case of accident or spill. Always transport in closed containers that are upright and secure. Ensure adequate ventilation.		
14.7	TRANSPORT IN BULK ACCORDING TO ANNEX I OF MARPOL 73/78 AND THE IBC CODE: Not available.		
SECTION 15 : REGULATORY INFORMATION			
15.1	EU SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC: The regulations applicable to this product generally are listed throughout this Safety Data Sheet. Restrictions on manufacture, placing on market and use: See section 1.2 Tactile warning of danger: Not applicable (product for professional or industrial use).		



	DERMAUTOLOGY DILUYENTE DIFUMINADOS Código: DA180/1				
	<p>Child safety protection: Not applicable (product for professional or industrial use).</p> <p>OTHER REGULATIONS:</p> <p>Control of the risks inherent in major accidents (Seveso III): See section 7.2</p> <p>Other local legislations: The receiver should verify the possible existence of local regulations applicable to the chemical.</p>				
15.2	<p>CHEMICAL SAFETY ASSESSMENT: A chemical safety assessment has not been carried out for this mixture.</p>				
SECTION 16 : OTHER INFORMATION					
	<p>TEXT OF THE PHRASES AND NOTES REFERENCED IN SECTIONS 2 AND/OR 3: Hazard statements according the Regulation (EU) No. 1272/2008~2020/1182 (CLP), Annex III: H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 Maybe fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. EUH066 Repeated exposure may cause skin dryness or cracking. H373i May cause damage to organs through prolonged or repeated exposure if inhaled.</p> <p>EVALUATION OF THE INFORMATION ON THE DANGER OF MIXTURES: See sections 9.1, 11.1 and 12.1.</p> <p>ADVICES ON ANY TRAINING APPROPRIATE FOR WORKERS: It is recommended for all staff that will handle this product to carry out a basic training in occupational risk and prevention, in order to provide understanding and interpretation of Safety Data Sheets and labelling of products as well.</p> <p>MAIN LITERATURE REFERENCES AND SOURCES FOR DATA:</p> <ul style="list-style-type: none"> · European Chemicals Agency: ECHA, http://echa.europa.eu/ · Access to European Union Law, http://eur-lex.europa.eu/ · Industrial Solvents Handbook, Ibert Mellan (Noyes Data Co., 1970). · Threshold Limit Values, (AGCIH, 2018). · European agreement on the international carriage of dangerous goods by road, (ADR 2021). · International Maritime Dangerous Goods Code IMDG including Amendment 39-18 (IMO, 2018). <p>ABBREVIATIONS AND ACRONYMS: List of abbreviations and acronyms that can be used (but not necessarily used) in this Safety Data Sheet:</p> <ul style="list-style-type: none"> · REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals. · GHS: Globally Harmonized System of Classification and Labelling of Chemicals of the United Nations. · CLP: European regulation on Classification, Labelling and Packaging of substances and chemical mixtures. · EINECS: European Inventory of Existing Commercial Chemical Substances. · ELINCS: European List of Notified Chemical Substances. · CAS: Chemical Abstracts Service (Division of the American Chemical Society). · UVCB: Substances of Unknown or Variable composition, complex reaction products or biological materials. · SVHC: Substances of Very High Concern. · PBT: Persistent, bioaccumulable and toxic substances. · vPvB: Very persistent and very bioaccumulable substances. · VOC: Volatile Organic Compounds. · DNEL: Derived No-Effect Level (REACH). · PNEC: Predicted No-Effect Concentration (REACH). · LD50: Lethal dose, 50 percent. · LC50: Lethal concentration, 50 percent. · UN: United Nations Organisation. · ADR: European agreement concerning the international carriage of dangerous goods by road. · RID: Regulations concerning the international transport of dangerous goods by rail. · IMDG: International Maritime code for Dangerous Goods. · IATA: International Air Transport Association. · ICAO: International Civil Aviation Organization. <p>SAFETY DATA SHEET REGULATIONS: Safety Data Sheet in accordance with Article 31 of Regulation (EC) No. 1907/2006 (REACH) and Annex of Regulation (EU) No. 2015/830.</p> <p>HISTORIC:</p> <table border="0"> <tr> <td>Version: 11</td> <td>Revision: 14/11/2019</td> </tr> <tr> <td>Version: 12</td> <td>Revision: 07/02/2022</td> </tr> </table> <p>Changes since previous Safety Data Sheet: # <i>Legislative, contextual, numerical, methodological and normative changes since the previous version of the present Safety Data Sheet are identified by a red-italic hash (#).</i></p>	Version: 11	Revision: 14/11/2019	Version: 12	Revision: 07/02/2022
Version: 11	Revision: 14/11/2019				
Version: 12	Revision: 07/02/2022				
<p>The information of this Safety Data Sheet, is based on the present state of knowledge and on current UE and national laws, as the users' working conditions are beyond our knowledge and control. The product is not to be used for other purposes than those specified, without first obtaining written handling instruction. It is always the responsibility of the user to take all necessary steps in order to fulfil the demand laid down in the local rules and legislation. The information in this Safety Data Sheet is meant as a description of the safety requirements of the product and it is not to be considered as a guarantee of the product's properties.</p>					