

# FASTDRY 4:1 GREY PRIMER

## DESCRIPTION:

Two-component acrylic primer. Mixed in 4:1 ratio with its specific hardener. Offers EXTRA fast drying and allows high film build per coat (up to 70 microns per coat).

Easy to use, can be applied over old paint or any other type of surface, including galvanized sheet metal or aluminium.

**VOG:** 2004/42/11B(C) (540)540

**SURFACE:** Steel, galvanized sheet metal, aluminium, putty, old paints.

## MODO DE USO:




P180-P220



4:1 Fastdry Hardener  
Pot life - 30°/20°C




0–15% by weight  
52”–20” Cup  
DIN4/20°C




1.5–1.8 mm. 2–4 bar  
2–3 coats=100–200 microns



50' / 20°C  
5'–10' / 60°C  
IR - 5' / 1 m



P320-P400



2004/42//11B  
(c)(540)540

## NEXT STEP::

Waterborne or solvent-based basecoat – Waterborne or solvent-based topcoat.

**SPECIFIC GRAVITY:** 1,6 ± 0,05

**RAW MATERIALS:** Hydroxylated acrylic resins, pigments, mineral fillers and solvents.

**SAFETY INFORMATION:** Consult Safety Data Sheet.

## SHELF LIFE:

12 months if stored under appropriate conditions.

## WARNINGS:

Store in a cool, dry place.

The technical information is based on our experience. We guarantee the quality of the product, however, since the conditions of use are beyond our control, we cannot accept any responsibility for the results obtained.