A-C-30



A brand of BASF – We create chemistry

Eco Balance clear coat, outstanding gloss level

Application: Key Features:			AraClass - Eco Balance clear coat for Glasurit waterborne basecoats. Eco effectiveness clear coat - outstanding gloss level For superior appearance.				
			3:1:1				
	Mixing Ratio		100 % by volume		A-C-30		
Ð	Hardener		33 % by volume		A-H-410, -H-420, -H-430, -H-440 Eco Balance top coat hardener		
¥∎	Reducer		33 % by volume		A-R-110, -R-120, -R-130 Eco Balance reducer		
Ş	Spray viscosity	at 20°C	DIN 4:	18-21 s	Potlife at 20°C	2 h	
Application:			Compliant gravity-feed				HVLP spray gun
Application pressure bar				2		2	
Nozzle pressure bar						0.7	
Nozzle size		1.3-1.4			1.3		
Number of spray coats		2					
Flash off at 20°C min		3-5 min. intermediate flash-off between the spraycoats. No flash-off before oven drying.					
Film thickness µm		40-60					

Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 $\mu m.$

2004/42/IIB(d)(420)419: The EU limit value for this product (product category: IIB.d) in ready to use form is max 420 g/litre of VOC. The VOC content of this product is 419 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

BASF Coatings GmbH - Automotive Refinish Coatings Solutions Europe - Glasuritstrasse 1 - 48165 Münster - Germany

A-C-30



A brand of BASF – We create chemistry

Eco Balance clear coat, outstanding gloss level

\bigcirc	Drying at 20 °C	8 h
\bigcirc	Drying at 60 °C	30 min
R	Infrared (short wave)	10 min
	Drying Remark	Drying times can be influenced by the selection of hardener, reducer and application. A-A-10 or A-A-12 additives can reduce drying times.

surface to cool down.

Polishing can be carried out when the specified drying time has been achieved, after allowing the

Remark



Safety advice:

The products are suitable for professional use only.

It cannot be ruled out that this product contains particles < 0.1 μ m.

2004/42/IIB(d)(420)419: The EU limit value for this product (product category: IIB.d) in ready to use form is max 420 g/litre of VOC. The VOC content of this product is 419 g/litres.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our products, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of the products for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights etc. given herein are for general information purpose only; they may change without prior information and do not constitute the agreed contractual quality of the products (product specification). The latest version supersedes all previous versions. You can obtain the latest version from our website at www.glasurit.com or directly from your sales partner. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.

BASF Coatings GmbH - Automotive Refinish Coatings Solutions Europe - Glasuritstrasse 1 - 48165 Münster - Germany