

## DERMASEALER POLYURETHANE SEALANT BLACK

DERMASEALER is a polyurethane sealant that, thanks to its formulation, has great flexibility properties and good adhesion to any surface. It can be used for any sector or application: Automotive, nautical, construction, wood, PVC, metals (including aluminum).

### MAIN FEATURES:

- Dried by reaction to moisture.
- Paintable with any paint finish.
- Good resistance to UV rays.

### TECHNICAL DATA:

**CHEMICAL BASE:** Polyurethane.

**COLOUR:** Black or white.

**CONSISTENCY:** Paste.

**SPECIFIC GRAVITY:** 1.16 g/cm<sup>3</sup>

**SOLVENTS PERCENTAGE:** 0%

**CURING TEMPERATURE RESISTANCE:** from -40°C to 80°C

### OTHER DATA:

**APPLICATION TEMPERATURE:** Between 5°C and 35°C with a relative humidity between 40% and 60%

**SUBSTRATE PREPARATION:** The surface must be completely clean, degreased and free of dust.

**FORMATION TIME PER COAT:** 45 minutes at 20 degrees with relative humidity of 50%

**STORAGE:** Dry and clean place at temperatures between 15°C and 30°C

### STATEMENT:

The information in this document is given in good faith based on our current knowledge and experience of the product when properly stored, handled and applied under normal conditions in accordance with our recommendations. In practice, differences in materials, substrates, and actual site conditions are such that no warranty regarding merchantability or fitness for a particular purpose, nor any liability arising out of any legal relationship, can be inferred from this data sheet. . The recommendations or suggestions contained in this data sheet are made without guarantee of results. We suggest that you test the suitability of the product for its intended application and purpose prior to use. Our liability for claims arising out of breach of warranty, negligence or otherwise is limited to the purchase price of the material.