



Printing date 08.05.2020 Revision: 08.05.2020

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Aerosol 2K 2in1 Headlight Clear
- · Article number (product ID.): REZ1163
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture: painting

FOR PROFESSIONAL USE ONLY

- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: Peter Kwasny GmbH Heilbronner Str. 96

D-74831 Gundelsheim

Tel.: 0049-(0)6269-95-20 E-mail: labor@kwasny.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number: Tel.:+49 6269 95 20
- · national:

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· K-Nr. 0001

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 C

· Signal word Danger

(Contd. on page 2)

Printing date 08.05.2020 Revision: 08.05.2020

Trade name: Aerosol 2K 2in1 Headlight Clear

(Contd. of page 1)

#### · Hazard-determining components of labelling:

Aliphatisches Polyisocyanat (HDI oligomers, isocyanurate)

n-butyl acetate

isobutyl acetate

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers

*Bis*(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H317 May cause an allergic skin reaction.H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

*P211* Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

*P273* Avoid release to the environment.

P302+P352 IF ON SKIN: Wash with plenty of water.

P312 Call a POISON CENTER/doctor if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · Additional information:

Without adequate ventilation, explosive atmosphere/gas mix may be created.

EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

EUH204 Contains isocyanates. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether  Flam. Gas 1, H220; Press. Gas (Comp.), H280	25-<50%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate Flam. Liq. 3, H226;  STOT SE 3, H336	10-<25%
CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119485796-17-xxxx	Aliphatisches Polyisocyanat (HDI oligomers, isocyanurate)  Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	5-<10%
CAS: 763-69-9 EINECS: 212-112-9 Reg.nr.: 01-2119463267-34-xxxx		2.5-<5%

(Contd. on page 3)

Printing date 08.05.2020 Revision: 08.05.2020

Trade name: Aerosol 2K 2in1 Headlight Clear

CAS: 108-65-6	2-methoxy-1-methylethyl acetate	Contd. of page 2 2.5-<5%
EINECS: 203-603-9 Reg.nr.: 01-2110475791-29-xxxx	🚸 Flam. Liq. 3, H226	
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers  ♠ Flam. Liq. 3, H226; ♠ STOT RE 2, H373; Asp. Tox. 1, H304; ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	1-<2.5%
CAS: 108-10-1 EINECS: 203-550-1 Reg.nr.: 01-2119473980-30-xxxx	4-methylpentan-2-one  Flam. Liq. 2, H225;	1-<2.5%
CAS: 110-19-0 EINECS: 203-745-1	isobutyl acetate  Flam. Liq. 2, H225;  STOT SE 3, H336	1-<2.5%
CAS: 53880-05-0 EINECS: 204-658-1	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers  • Skin Sens. 1, H317; STOT SE 3, H335	<i>≥</i> 0.1-<1%
CAS: 41556-26-7 EINECS: 255-437-1 Reg.nr.: no Reach-No. availlable	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	<i>≥</i> 0.25-<1%

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

*In case of unconsciousness place patient stably in side position for transportation.* 

- $\cdot \textit{After skin contact:} \ \textit{Immediately wash with water and soap and rinse thoroughly}.$
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures
  - Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Printing date 08.05.2020 Revision: 08.05.2020

Trade name: Aerosol 2K 2in1 Headlight Clear

(Contd. of page 3)

#### · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients with	limit values that	t require monit	toring at th	ie workplace:
--------------------	-------------------	-----------------	--------------	---------------

### 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

### 1330-20-7 xylene, mixture of isomers

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

### 108-10-1 4-methylpentan-2-one

WEL Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm Sk, BMGV

### · Ingredients with biological limit values:

#### 1330-20-7 xylene, mixture of isomers

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

(Contd. on page 5)

Printing date 08.05.2020 Revision: 08.05.2020

Trade name: Aerosol 2K 2in1 Headlight Clear

(Contd. of page 4)

### 108-10-1 4-methylpentan-2-one

BMGV 20 µmol/L

Medium: urine

Sampling time: post shift

Parameter: 4-methylpentan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Protection of hands:

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

 $\cdot$  **Eye protection:** Not required.

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- $\cdot \, Appearance:$

Form: Aerosol

Colour: According to product specification

• Odour: Characteristic• Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

**Melting point/freezing point:** Undetermined. **Initial boiling point and boiling range:** -24.9 °C

· Flash point: 23 °C

Without propellant gas.

(Contd. on page 6)

Printing date 08.05.2020 Revision: 08.05.2020

Trade name: Aerosol 2K 2in1 Headlight Clear

	(Contd. of page
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive ai vapour mixtures are possible.  Not determined.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	18.6 Vol %
· Vapour pressure at 20 °C:	3,400 hPa
Density at 20 °C:	0.834 g/cm³
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	77.6 %
	With propellant gas. Content given by weight.
VOC (EU)	77.60 %
Solids content:	33.1 %
9.2 Other information	No further relevant information available.

### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative | LC50/4 h | 20.2-20.6 mg/l

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 08.05.2020 Revision: 08.05.2020

Trade name: Aerosol 2K 2in1 Headlight Clear

(Contd. of page 6)

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- $\cdot \textit{Additional ecological information:}$
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Ikke relevant.
- · 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 10\* packaging containing residues of or contaminated by hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

### **SECTION 14: Transport information**

· 14.1 UN-Number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR 1950 AEROSOLS · IMDG AEROSOLS · IATA AEROSOLS, flammable

(Contd. on page 8)

Printing date 08.05.2020 Revision: 08.05.2020

Trade name: Aerosol 2K 2in1 Headlight Clear

	(Contd. of pa
14.3 Transport hazard class(es)	
ADR	
2	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
<u> </u>	
Class	2.1
Label	2.1
14.4 Packing group	Void
ADR, IMDG, IATA	voia not classified
14.5 Environmental hazards:	Not applicable.
<u> </u>	
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	not classified
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW2 Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 little Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2
14.7 Transport in bulk according to Anne Marpol and the IBC Code	x II of Not applicable.
	1101 иррисионе.
Transport/Additional information:	
ADR	11
Limited quantities (LQ)  Excepted quantities (EQ)	1L Code: E0
Excepted quantities (EQ)	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
<i>IMDG</i>	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

Printing date 08.05.2020 Revision: 08.05.2020

Trade name: Aerosol 2K 2in1 Headlight Clear

(Contd. of page 8)

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

### · Department issuing SDS: Product safety department

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Printing date 08.05.2020 Revision: 08.05.2020

### Trade name: Aerosol 2K 2in1 Headlight Clear

(Contd. of page 9)

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - inhalation – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3