

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**UV Putty Fine**  
**UV Putty Coarse**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Filler

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

(GB)

Doxa Technological Systems International BV  
Holsteinstraat 16  
8028 RT Zwolle  
The Netherlands  
T +31 38 4676600  
F + 31 38 4676699

Qualified person's e-mail address: [info@chemical-check.de](mailto:info@chemical-check.de), [k.schnurbusch@chemical-check.de](mailto:k.schnurbusch@chemical-check.de) Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+31-38-4676600 (Week days available between 08:00 & 17:00)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Aquatic Chronic	2	H411-Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**



## Warning

H319-Causes serious eye irritation. H315-Causes skin irritation. H317-May cause an allergic skin reaction. H411-Toxic to aquatic life with long lasting effects.

P261-Avoid breathing dust. P273-Avoid release to the environment. P280-Wear protective gloves / eye protection / face protection. P314-Get medical advice / attention if you feel unwell.

(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate  
 exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate  
 Hexamethylene diacrylate  
 Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate  
 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid

## 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

<b>Hexanoic acid, 6-[[[[[1,3,3-trimethyl-5-[[[[6-oxo-6-[2-[(1-oxo-2-propenyl)oxy]ethoxy]hexyl]oxy]carbonyl]amino]cyclohexyl]methyl]amino]carbonyl]oxy]-, 2-[(1-oxo-2-propenyl)oxy]ethylester</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	---
<b>CAS</b>	119107-13-0
<b>content %</b>	10-<25
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Irrit. 2, H315 Eye Irrit. 2, H319
<b>Hexamethylene diacrylate</b>	
<b>Registration number (REACH)</b>	01-2119484737-22-XXXX
<b>Index</b>	607-109-00-8
<b>EINECS, ELINCS, NLP</b>	235-921-9
<b>CAS</b>	13048-33-4
<b>content %</b>	5-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411
<b>exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate</b>	
<b>Registration number (REACH)</b>	01-2119957862-25-XXXX
<b>Index</b>	607-133-00-9

Page 3 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 09.12.2020 / 0002  
 Replacing version dated / version: 24.04.2020 / 0001  
 Valid from: 09.12.2020  
 PDF print date: 09.12.2020  
 UV Putty Fine  
 UV Putty Coarse

<b>EINECS, ELINCS, NLP</b>	227-561-6
<b>CAS</b>	5888-33-5
<b>content %</b>	5-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

<b>1H-Azepine-1-propanoic acid, hexahydro-, 2,2-bis[[[(1-oxo-2-propen-1-yl)oxy]methyl]butyl ester</b>	
<b>Registration number (REACH)</b>	---
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	690-398-8 (REACH-IT List-No.)
<b>CAS</b>	73003-78-8
<b>content %</b>	5-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Irrit. 2, H315 Eye Irrit. 2, H319

<b>4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, esters with acrylic acid</b>	
<b>Registration number (REACH)</b>	01-2119490020-53-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	500-130-2 (NLP)
<b>CAS</b>	55818-57-0
<b>content %</b>	5-<10
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Sens. 1, H317 Aquatic Chronic 2, H411

<b>Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate</b>	
<b>Registration number (REACH)</b>	01-2119987994-10-XXXX
<b>Index</b>	---
<b>EINECS, ELINCS, NLP</b>	282-810-6
<b>CAS</b>	84434-11-7
<b>content %</b>	1-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Skin Sens. 1B, H317 Aquatic Chronic 2, H411

<b>(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate</b>	
<b>Registration number (REACH)</b>	01-2119484613-34-XXXX
<b>Index</b>	607-249-00-X
<b>EINECS, ELINCS, NLP</b>	256-032-2
<b>CAS</b>	42978-66-5
<b>content %</b>	0,5-<2,5
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

<b>Acrylic acid</b>	<b>Substance for which an EU exposure limit value applies.</b>
<b>Registration number (REACH)</b>	01-2119452449-31-XXXX
<b>Index</b>	607-061-00-8
<b>EINECS, ELINCS, NLP</b>	201-177-9
<b>CAS</b>	79-10-7
<b>content %</b>	0,005-<0,3
<b>Classification according to Regulation (EC) 1272/2008 (CLP)</b>	Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Acute Tox. 4, H302 Skin Corr. 1A, H314 Aquatic Acute 1, H400 (M=1) Eye Dam. 1, H318

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.  
For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
The substances named in this section are given with their actual, appropriate classification!  
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

#### Ingestion

Rinse the mouth thoroughly with water.  
Do not induce vomiting. Consult doctor immediately.  
Give water to drink.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.  
eyes, reddened  
watering eyes  
reddening of the skin  
Dermatitis (skin inflammation)  
Allergic reaction

### 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

#### Unsuitable extinguishing media

High volume water jet

### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon  
Metal oxides  
Oxides of phosphorus  
Oxides of nitrogen  
Halogenated compounds  
Toxic gases

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Do not take any measures that are associated with personal risk or have not been sufficiently trained.

Keep unprotected persons away.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

## 6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

## 6.3 Methods and material for containment and cleaning up

Pick up mechanically and dispose of according to Section 13.

Avoid build up of dust.

Fill the absorbed material into lockable containers.

## 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

# SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

## 7.1 Precautions for safe handling

### 7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Protect from direct sunlight and warming.

Store in a well ventilated place.

Store in a dry place.

Store upright.

Recommended storage temperature:

20 - 25°C

## 7.3 Specific end use(s)

No information available at present.

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

GB	Chemical Name	Acrylic acid	Content
			Content %:0,005-<0,3
	WEL-TWA: 10 ppm (29 mg/m <sup>3</sup> ) (WEL, EU)	WEL-STEL: 20 ppm (59 mg/m <sup>3</sup> ) (10) (WEL, EU)	---
	Monitoring procedures:	- Draeger - Acid Test (81 01 121)	
	BMGV: ---		Other information: ---
GB	Chemical Name	Silicon dioxide - amorphous	Content %:
	WEL-TWA: 6 mg/m <sup>3</sup> (total inh. dust), 2,4 mg/m <sup>3</sup> (resp. dust)	WEL-STEL: ---	---
	Monitoring procedures:	---	
	BMGV: ---		Other information: ---
GB	Chemical Name	Talc	Content %:

Page 6 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 09.12.2020 / 0002  
 Replacing version dated / version: 24.04.2020 / 0001  
 Valid from: 09.12.2020  
 PDF print date: 09.12.2020  
 UV Putty Fine  
 UV Putty Coarse

WEL-TWA: 1 mg/m3 (res. dust)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	

<b>Chemical Name</b>	China stone	Content %:
WEL-TWA: 2 mg/m3 (res. dust)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	

<b>Chemical Name</b>	general dust limit	Content %:
WEL-TWA: 10 mg/m3 (inhal. dust), 4 mg/m3 (respir. dust)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	

Hexamethylene diacrylate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,007	mg/l	
	Environment - marine		PNEC	0,001	mg/l	
	Environment - sewage treatment plant		PNEC	2,7	mg/l	
	Environment - sediment, freshwater		PNEC	0,493	mg/kg dw	
	Environment - sediment, marine		PNEC	0,049	mg/kg dw	
	Environment - soil		PNEC	0,094	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	2,1	mg/kg bw/d	
Consumer	Human - dermal	Long term, systemic effects	DNEL	1,66	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	7,2	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	24,5	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	2,77	mg/kg bw/d	

exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,001	mg/l	
	Environment - marine		PNEC	0	mg/l	
	Environment - sediment, freshwater		PNEC	0,145	mg/kg dw	
	Environment - sediment, marine		PNEC	0,015	mg/kg dw	
	Environment - soil		PNEC	0,029	mg/kg dw	
	Environment - sewage treatment plant		PNEC	2	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,007	mg/l	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	1,45	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,83	mg/kg bw/d	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,83	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4,9	mg/m3	

Workers / employees	Human - dermal	Long term, systemic effects	DNEL	1,39	mg/kg bw/d	
---------------------	----------------	-----------------------------	------	------	------------	--

Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	1,01	µg/l	
	Environment - marine		PNEC	0,101	µg/l	
	Environment - water, sporadic (intermittent) release		PNEC	10,1	µg/l	
	Environment - sediment, freshwater		PNEC	0,24	mg/kg dw	
	Environment - sediment, marine		PNEC	0,024	mg/kg dw	
	Environment - soil		PNEC	0,0475	mg/kg dw	

Silicon dioxide - amorphous						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	4	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. EN 14042.  
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Chemical resistant protective gloves (EN 374).  
 If applicable

Page 8 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 09.12.2020 / 0002  
 Replacing version dated / version: 24.04.2020 / 0001  
 Valid from: 09.12.2020  
 PDF print date: 09.12.2020  
 UV Putty Fine  
 UV Putty Coarse

Protective gloves made of butyl (EN 374).  
 Protective Neoprene® / polychloroprene gloves (EN 374).  
 Protective nitrile gloves (EN 374).  
 Protective PVC gloves (EN 374).  
 Minimum layer thickness in mm:  
 >= 0,5  
 Permeation time (penetration time) in minutes:  
 240 - 480  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.  
 Protective hand cream recommended.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 Normally not necessary.  
 If air supply is not sufficient, wear protective breathing apparatus.  
 Filter A P2 (EN 14387), code colour brown, white  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Solid
Colour:	According to specification
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	n.a.
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	Not determined
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Not determined
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	n.a.
Explosive properties:	Product is not explosive.
Oxidising properties:	No

### 9.2 Other information

Miscibility: Not determined



Page 9 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 09.12.2020 / 0002  
 Replacing version dated / version: 24.04.2020 / 0001  
 Valid from: 09.12.2020  
 PDF print date: 09.12.2020  
 UV Putty Fine  
 UV Putty Coarse

Fat solubility / solvent: Not determined  
 Conductivity: Not determined  
 Surface tension: Not determined  
 Solvents content: Not determined

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

Hazardous polymerisation will not occur during storage and handling under normal conditions.

### 10.4 Conditions to avoid

Strong heat

### 10.5 Incompatible materials

Avoid contact with strong alkalis.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

### 10.6 Hazardous decomposition products

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

UV Putty Fine UV Putty Coarse						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Hexamethylene diacrylate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>3650	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2

Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Skin Sens. 1
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative

**exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4350	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1B
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 487 (In Vitro Mammalian Cell Micronucleus Test)	Negative
Aspiration hazard:						No

**Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1B
Germ cell mutagenicity:					OECD 487 (In Vitro Mammalian Cell Micronucleus Test)	Negative
Symptoms:						itching

**(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit		Eye Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Sensitising (skin contact)

Page 11 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 09.12.2020 / 0002  
 Replacing version dated / version: 24.04.2020 / 0001  
 Valid from: 09.12.2020  
 PDF print date: 09.12.2020  
 UV Putty Fine  
 UV Putty Coarse

Germ cell mutagenicity:				Mammalian	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	250	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	Analogous conclusion

<b>Acrylic acid</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1300	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	295-750	mg/kg	Rabbit		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Corr. 1A
Serious eye damage/irritation:						Eye Dam. 1
Germ cell mutagenicity:				Rat	OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Aspiration hazard:						No
Symptoms:						respiratory distress, cornea opacity, coughing, mucous membrane irritation

<b>Silicon dioxide - amorphous</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5110	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	IUCLID Chem. Data Sheet (ESIS)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	IUCLID Chem. Data Sheet (ESIS)	Not sensitising
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:	NOAEL	>497	mg/kg bw/d			No indications of such an effect.
Aspiration hazard:						No
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,035	mg/l			Negative

<b>Talc</b>						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat		

Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Skin corrosion/irritation:						Not irritant
Respiratory or skin sensitisation:						Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:				Rat		Negative
Symptoms:						mucous membrane irritation

**China stone**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat		
Serious eye damage/irritation:						Mechanical irritation possible.
Aspiration hazard:						No

**SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

**UV Putty Fine  
UV Putty Coarse**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

**Hexamethylene diacrylate**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC50	30min	~270	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.2. Persistence and degradability:		28d	60-70	%	activated sludge	OECD 310 (Ready Biodegradability - CO2 in sealed vessels (Headspace Test))	Readily biodegradable

12.1. Toxicity to daphnia:	EC50	48h	2,7	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to fish:	LC50	96h	0,38	mg/l	Oryzias latipes	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL		0,072	mg/l	Oryzias latipes	OECD 210 (Fish, Early-Life Stage Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,14	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	1,09	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	

**exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	0,704	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to algae:	EC50	72h	1,98	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	57	%		OECD 310 (Ready Biodegradability - CO <sub>2</sub> in sealed vessels (Headspace Test))	Not readily biodegradable
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	0,092	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	

**Ethyl phenyl(2,4,6-trimethylbenzoyl)phosphinate**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
12.1. Toxicity to algae:	EC50	72h	1,01	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to fish:	LC50	96h	1,89	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:		28d	<10	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily biodegradable

12.1. Toxicity to daphnia:	EC50	48h	2,26	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

**(1-methyl-1,2-ethanediyl)bis[oxy(methyl-2,1-ethanediyl)] diacrylate**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	48	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	
12.1. Toxicity to fish:	LC50	96h	>4,5- <10	mg/l	Leuciscus idus	DIN 38412 T.15	
Toxicity to bacteria:	EC50	30min	>10000	mg/l	Pseudomonas putida		
Other information:	BOD/COD		>60	%			

**Acrylic acid**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	ErC50	72h	0,04	mg/l	Scenedesmus subspicatus		
12.3. Bioaccumulative potential:	BCF		3,162				Low, calculated value
12.1. Toxicity to fish:	LC50	96h	27	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	222	mg/l	Brachydanio rerio		
12.1. Toxicity to fish:	LC50	96h	27	mg/l	Salmo gairdneri		
12.1. Toxicity to daphnia:	EC50	48h	47	mg/l	Daphnia magna		
12.2. Persistence and degradability:			81	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable

**Silicon dioxide - amorphous**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	>10000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.1. Toxicity to algae:	IC50	72h	440	mg/l	Pseudokirchnerie lla subcapitata	IUCLID Chem. Data Sheet (ESIS)	
12.1. Toxicity to algae:	NOEC/NOEL	72h	60	mg/l	Pseudokirchnerie lla subcapitata	IUCLID Chem. Data Sheet (ESIS)	
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

**Talc**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Water solubility:			<0,1	%			

Page 15 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 09.12.2020 / 0002  
 Replacing version dated / version: 24.04.2020 / 0001  
 Valid from: 09.12.2020  
 PDF print date: 09.12.2020  
 UV Putty Fine  
 UV Putty Coarse

12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

China stone							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods., Mechanical precipitation possible.
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l			
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	LC50	48h	>1100	mg/l	Daphnia magna		References
12.1. Toxicity to algae:	IC50		>1000	mg/l			
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:							Not biodegradable
Water solubility:							Insoluble

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Untamined packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

## SECTION 14: Transport information

### General statements

14.1. UN number:

3077

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

Page 16 of 18  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 09.12.2020 / 0002  
 Replacing version dated / version: 24.04.2020 / 0001  
 Valid from: 09.12.2020  
 PDF print date: 09.12.2020  
 UV Putty Fine  
 UV Putty Coarse

UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (HEXAMETHYLENE DIACRYLATE,EXO-1,7,7-TRIMETHYLBICYCLO[2.2.1]HEPT-2-YL ACRYLATE)

14.3. Transport hazard class(es): 9  
 14.4. Packing group: III  
 Classification code: M7  
 LQ: 5 kg  
 14.5. Environmental hazards: environmentally hazardous  
 Tunnel restriction code: -



### Transport by sea (IMDG-code)

14.2. UN proper shipping name:  
 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (HEXAMETHYLENE DIACRYLATE,EXO-1,7,7-TRIMETHYLBICYCLO[2.2.1]HEPT-2-YL ACRYLATE)

14.3. Transport hazard class(es): 9  
 14.4. Packing group: III  
 EmS: F-A, S-F  
 Marine Pollutant: Yes  
 14.5. Environmental hazards: environmentally hazardous



### Transport by air (IATA)

14.2. UN proper shipping name:  
 Environmentally hazardous substance, solid, n.o.s. (HEXAMETHYLENE DIACRYLATE,EXO-1,7,7-TRIMETHYLBICYCLO[2.2.1]HEPT-2-YL ACRYLATE)

14.3. Transport hazard class(es): 9  
 14.4. Packing group: III  
 14.5. Environmental hazards: environmentally hazardous



### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.  
 All persons involved in transporting must observe safety regulations.  
 Precautions must be taken to prevent damage.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.  
 Minimum amount regulations have not been taken into account.  
 Danger code and packing code on request.  
 Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:  
 Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
E2		200	500

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): < 0,3 %

Observe incident regulations.

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 11, 12, 15  
 Employee training in handling dangerous goods is required.



These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Aquatic Chronic 2, H411	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.

H226 Flammable liquid and vapour.

H317 May cause an allergic skin reaction.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation

Skin Irrit. — Skin irritation

Skin Sens. — Skin sensitization

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Aquatic Acute — Hazardous to the aquatic environment - acute

STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Flam. Liq. — Flammable liquid

Acute Tox. — Acute toxicity - inhalation

Acute Tox. — Acute toxicity - dermal

Acute Tox. — Acute toxicity - oral

Skin Corr. — Skin corrosion

Eye Dam. — Serious eye damage

### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight  
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
EC European Community  
ECHA European Chemicals Agency  
EEC European Economic Community  
EINECS European Inventory of Existing Commercial Chemical Substances  
ELINCS European List of Notified Chemical Substances  
EN European Norms  
EPA United States Environmental Protection Agency (United States of America)  
etc. et cetera  
EU European Union  
EVAL Ethylene-vinyl alcohol copolymer  
Fax. Fax number  
gen. general  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
GWP Global warming potential  
IARC International Agency for Research on Cancer  
IATA International Air Transport Association  
IBC (Code) International Bulk Chemical (Code)  
IMDG-code International Maritime Code for Dangerous Goods  
incl. including, inclusive  
IUCLID International Uniform Chemical Information Database  
IUPAC International Union for Pure Applied Chemistry  
LC50 Lethal Concentration to 50 % of a test population  
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
LQ Limited Quantities  
MARPOL International Convention for the Prevention of Marine Pollution from Ships  
n.a. not applicable  
n.av. not available  
n.c. not checked  
n.d.a. no data available  
OECD Organisation for Economic Co-operation and Development  
org. organic  
PBT persistent, bioaccumulative and toxic  
PE Polyethylene  
PNEC Predicted No Effect Concentration  
ppm parts per million  
PVC Polyvinylchloride  
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
SVHC Substances of Very High Concern  
Tel. Telephone  
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
VOC Volatile organic compounds  
vPvB very persistent and very bioaccumulative  
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.